

CERTIFICATE OF COMPLIANCE

Certificate Number 20181029-E308146
Report Reference E308146-20141212
Issue Date 2018-OCTOBER-29

Issued to: KNICK ELEKTRONISCHE MESSGERATE GMBH & CO
KG
BEUCKESTRASSE 22
14163 BERLIN GERMANY

This is to certify that representative samples of PROCESS CONTROL EQUIPMENT FOR USE IN HAZARDOUS LOCATIONS
See Addendum Page.

Have been investigated by UL in accordance with the Standard(s) indicated on this Certificate.

Standard(s) for Safety: ANSI/ISA 12.12.01 (Nonincendive Electrical Equipment for Use in Class I and II, Division 2 and Class III, Divisions 1 and 2 Hazardous (Classified) Locations) and CAN/CSA C22.2 No. 213-M1987 (Non-incendive Electrical Equipment for Use in Class I, Division 2 Hazardous Locations)

Additional Information: See the UL Online Certifications Directory at www.ul.com/database for additional information

Only those products bearing the UL Certification Mark should be considered as being covered by UL's Certification and Follow-Up Service.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Director North American Certification Program
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number 20181029-E308146
Report Reference E308146-20141212
Issue Date 2018-OCTOBER-29

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Open Type Programmable Controllers for use in Hazardous Locations, Class I, Division 2, Groups A, B, C and D Hazardous Locations.

Loop-Powered Isolator and Loop-Powered Splitter

Loop-powered isolators for standard signals, 1 channel, types:


ProLine P22401P1
ProLine P22401P1-PX
ProLine P22401P1-SP-PX
ProLine P22401P1-PL-PX
ProLine P22401P1-PL-SP-PX

Loop-powered splitter for standard signals, 2 channels, type:

ProLine P22412P1

Loop-powered isolators for standard signals, 2 channels, types:

ProLine P22402P1
ProLine P22402P1-PX
ProLine P22402P1-SP-PX
ProLine P22402P1-PL-PX
ProLine P22402P1-PL-SP-PX



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>

